

TABLE of CONTENTS

1.	SCOPE	7
2.	KNOWLEDGE PREREQUISITES	7
3.	STRUCTURE OF THIS MANUAL	8
4.	INSTALLING YOUR ROBOBUG TM EDUCATION SOFTWARE	8
4.1	New ROBOBUG Distribution Libraries	8
5.	INSECT AND OTHER HEXAPOD GAITS	9
5.1	Leg Designation	10
5.2	Gait Pattern Diagrams	10
5.3	Gaits as Swing Permutations	11
5.4	Tripod Walk	11
5.5	“One Leg at a Time” Metachronal Wave	12
5.5.1	“Two Legs At A Time” Metachronal Wave	13
5.5.2	The Oar Gait	13
6.	STATIC STABILITY OF A GAIT	14
7.	DYNAMIC STABILITY OF A GAIT	15
8.	ROBOBUG TM LEG MECHANISM AND STEP CYCLE	15
8.1	Step Cycle	16
8.2	ROBOBUG Leg and Servo Numbering	17
9.	ROBOT CONNECTIONS DURING PROGRAM DEVELOPMENT	17
10.	ROBOBUG TM EXPERIMENT SUMMARY	18
10.1	Leg Experiments	18
10.2	Bug Pose Experiments	19
10.3	ROBOBUG TM Marching in Place	20
10.4	Forward, Backward and Turning Gaits for ROBOBUG TM	21
11.	ROBOBUG LEG EXPERIMENTS	22
11.1	Leg Experiment 1	22
11.1.1	Experiments with legx1.c	23
11.2	Leg Experiment 2	24
11.2.1	Description of ROBOBUG TM Library Function bugservo ()	24
11.2.2	Experiments with legx2.c	25
11.3	Leg Experiment 3	25
11.3.1	Experiments with legx3.c	26
11.4	Generate a Step Cycle	26
11.5	Multiple Leg Lift, Static Stability, and Swing Experiments	27
12.	ROBOBUG TM POSTURES	28
13.	ROBOBUG TM MARCHING IN PLACE	31
13.1	Solution Sketch of the One-Legged Metachronal March in Place (march1.c)	31
13.2	Two-Legged Metachronal March in Place (Solution: march2.c)	33
13.3	Oar Gait March in Place	34
13.4	Tripod March	34
14.	PROGRAMMING ROBOBUG TM GAITS	35
14.1	Transformation of Gait Swing Sequences into Leg Phases	35
14.1.1	Leg Phase Calculations	36

14.2	Walking Forward	38
14.3	Walking Backward.....	39
14.4	Turning.....	39
14.5	A GAITS DEMO PROGRAM	40
14.6	Input Gait Parameters to a General Walking Program	40
15.	FURTHER STUDY	44
16.	ROBOBUG™ SOFTWARE REFERENCE (IVAN ZAPATA COAUTHOR) ..	45
16.1	Overview of the ROBOBUG™ Software Library.....	45
16.2	ROBOBUG™ Control and Walking Functions.....	45
16.2.1	Walking controller	46
	Parameter Definitions	46
16.3	Servo Control Functions	47
16.4	Calibrating the Legs.....	48
	Leg Lift-Servo.....	49
	Leg Swing-Servo	49
16.5	Other Macro / Symbol Definitions	49
16.6	Analog Port Routines.....	50

LIST of FIGURES

Figure 1.	Hexapod legs labeled according to the ROBOBUG™ convention. The arrow on the body points towards the head. The first letter stands for L, left, R, right and the second letter for F, front, M, middle, R, rear.	10
Figure 2.	Tripod gait pattern of a hexapod walking versus time. The black bars indicate the stance phase, where the foot is on the ground. The gaps between the stance phase indicate the foot is off the ground and swinging.	11
Figure 3.	The tripod walk used by ants and other insects for fast and efficient walking is both statically and dynamically stable.	12
Figure 4.	A single-leg metachronal gait swings each leg in sequence, from back-to-front, first on one side and then on the other. The red colored leg indicates the leg currently swinging off the ground. The black legs indicates the stance phase for that leg. If you reverse the arrows, you will get another metachronal wave pattern from front-to-back.	12
Figure 5.	A single-leg metachronal gait that swings legs on alternating sides, from back-to-front, first on one side and then on the other. The red colored leg indicates the leg currently swinging. If you reverse the arrows, you will get a similar gait.....	13
Figure 6.	A two-legged metachronal gait swings two legs at a time and consists of two simultaneous single leg metachronal patterns out of phase by five leg positions.	13
Figure 7.	A two-legged gait that swings the four contralateral outside legs metachronally, alternating with an oar sweep by the contralateral middle legs.	14
Figure 8.	The double metachronal wave illustrating, respectively, the front, center and back positions of the RF, RM, LR, LM legs during the stance phase. If the center of mass falls within the intersection of the three parallelograms, then hexapod is statically stable at all times during the motion. The rectangle formed by the two blue lines and the sides of the hexapod indicate where the center-of-mass must fall for a statically stable stance phase. ..	14

Figure 9. Elevated view of ROBOBUG™ showing the rear legs in center position for both the *lift-servos* and *swing-servos*. During calibration, position the legs as shown and then take the reading of the center position of each *lift-servo* and *swing-servo* center position..... 16

Figure 10. This diagram illustrates the ROBOBUG™ leg numbering and naming scheme and identifies the corresponding servo numbers for each leg. The lower numbered servo moves the leg up and down while the higher numbered servo swings the leg back and forth. The direction of the arrow indicates the front of the robot as you look down from the top. 17

Figure 11. Source Code listing of legx1.c..... 22

Figure 12. This program lifts the right front leg for 3 seconds, puts it back down and 3 seconds later “relaxes” the legs. 24

Figure 13. A program to lift the front right leg up and down four times..... 25

Figure 14. This program swings the right front leg for 1 second and then back for 1 second without lifting it up. 26

Figure 15. A gait pattern diagram representing a single step cycle for the right-front leg with the other legs on the ground. The dashed line represents the *swing phase* and the solid bar the *stance phase* of the front-leg during the single forward step. *Note, this is not a walking pattern.* The other legs just stay on the ground in the program example..... 26

Figure 16. A program that generates a single step cycle for the right front leg..... 27

Figure 17. A program that lifts the two front legs at the same time. 28

Figure 18. A program to cause ROBOBUG™ to rear up its head and lower its back side in a defensive posture. 29

Figure 19. The program sketch indicates how to program ROBOBUG™ to sequence its legs in the one-legged metachronal pattern without the stance phase..... 33

Figure 20. This program allows you to implement various gaits on ROBOBUG™. 39

Figure 21. This general purpose gait program allows you to input the 10 gait parameter through a serial port. 43

Figure 22. This portion of the calbug.h file defines three positions for the right-middle leg servos, servos 6 (*lift servo*) and 7 (*swing servo*). Two of the values indicate the extremities of motion and a third an intermediate value dictated by the leg structure and desired motion pattern. 48

Figure 23. Elevated view of ROBOBUG™ showing the rear legs in center position for both the *lift-servos* and *swing-servos*. During calibration, position the legs as shown and then take the reading of the center position of each *lift-servo* and *swing-servo* center position..... 49

LIST of TABLES

Table 1. Directories in buged01 8

Table 2. Step Cycle Phases 16

Table 3. Leg Experiments (Section 11) 19

Table 4. ROBOBUG™ Postures (Section)..... 19

Table 5. ROBOBUG™ Marching in Place..... 21

Table 6. ROBOBUG™ Forward Gaits 21

Table 7. ROBOBUG™ Forward Gaits 35